



Канатный электротельфер Т78 Уменьшенная строительная высота, полиспаст 4/1

Тип	Полиспаст 4/1		Размеры, mm																			
	Высота подъема, m	Грузоподъемность, kg	Скорость подъема m/min				L2	L3	L4	L5	L6	H1	H2	H3	B	B1	B2	B3	C	D		
			4	6	4/1	6/1																
T783...	H3	6	2000	L1				412	280	85	12	70	253	518	45	130... 150	530	45	387	520	175	
	H4	9		914	954	512	185															39
	H5	12		1114	1154	612	285															-85
T784...	H3	6	4000	L1				467	280	43	50	80	253	458	40.5	130... 150	560	50	504	680	175	
	H4	9		1026	1090	567	143															0
	H5	12		1226	1290	667	243															-53
T785...	H3	6	6300	L1				492	310	52	56	80	285	475	40.5	130... 150	600	56	510	740	210	
	H4	9		1086	1153	602	162															0
	H5	12		1306	1373	712	272															-57
T786...	H3	6	10000	L1				500	354	35	68	90	305	445	57.5	130... 150	720	71	616	945	250	
	H4	9		1115	1203	605	140															15
	H5	12		1325	1413	710	240															-60

Тип	Полиспаст 4/1		Скорость подъема m/min				
	Высота подъема, m	Грузоподъемность, kg	4	6	4/1	6/1	
			Вес, kg				
T783...	H3	6	2000	320		343	
	H4	9		355		378	
	H5	12		390		413	
T784...	H3	6	4000	510		557	
	H4	9		570		617	
	H5	12		630		677	
T785...	H3	6	6300	605	615	670	
	H4	9		665	675	730	
	H5	12		725	735	790	
T786...	H3	6	10000	758		853	
	H4	9		826		921	
	H5	12		896		991	